



APPLICATIONS

- Medical and Criminal Forensics labeling
- Advanced Security Identification
- Courtroom Systems
- Patient Name & Information
- Video Source Label
- Room Label
- Video Conferencing

HIGH QUALITY CHARACTERS: The TLR500 provides 20 rows of characters with 32 characters per row. Each character is well defined for easy viewing. The characters record onto tape or digital recordings with excellent playback readability.

NON-VOLATILE MEMORY: The TLR500 has one page of memory for the text. This page is backed up in EEPROM based non-volatile memory so the unit will remember the text and the settings when power is off.

BASIC TITLE APPLICATIONS: The TLR500 was designed for very simple title applications where short lines of text, like a name or room number, need to be overlaid onto the video signal.

KEYBOARD FUNCTIONALITY: All of the features and functions are available from simple keyboard commands. The user manual includes a list of all available functions and settings.

OPERATION WITHOUT THE KEYBOARD: The TLR500 requires a keyboard to initially type the text onto the video. Once the text is programmed, the keyboard can be removed. This allows continuous display of the same text. A front panel switch allows the text overlay to be turned off or on as needed without affecting the stored text.

COLOR CHARACTERS: The Character color may be set to one of eight colors on a character by character basis. Color selection is by an easy to use keyboard based menu.

FEATURES

- Provides 20 rows of 32 characters
- Eight character colors
- Eight background colors plus transparent
- Character blink/flash function
- Digital Signal Processing (DSP) assures accurate and repeatable performance
- Composite and S-Video inputs with automatic selection
- Composite and S-Video simultaneous outputs
- Available for NTSC or PAL video systems
- EEPROM memory stores text when power is off
- Memory is rated for over 50 years and 1,000,000 writes.
- Low cost
- Small size
- Rack mount option available
- Can operate from +5VDC for mobile applications
- +5VDC power supply included
- Keyboard not included (available separately)

FLEXIBLE BACKGROUND COLORS: Each character may have a rectangular background color behind it for ease of reading in low contrast situations. The background may also be set to transparent for applications where the maximum image area needs to be seen. The background can be set to one of eight colors or transparent and can be set on a character by character basis.

BLINKING CHARACTERS: To get attention, a blink (flash) function is available and can be set on a character by character basis.

FLEXIBLE CONNECTIONS: The TLR500 can accept either composite video or S-video input signals and will automatically select the first one it finds available. The unit will always produce both composite and S-Video output signals regardless of input signal type. Units are available for both the NTSC and PAL video standards.

BOARD AND CUSTOM PRODUCTS: MicroImage Video Systems offers many of its products, such as the TLR500, as board level (i.e. BL-TLR500-00) for OEM applications. We can create units with custom features as well as custom designed boards.

MORE INFORMATION? Additional product information, specifications, user manuals and application notes are available on our website, including the latest available features.

STANDARD KEYBOARD INTERFACE? The TLR500 works with most industry standard AT keyboards that use the 6 pin mini-DIN (PS/2) style connector.



A division of World Video Sales Company, Inc.

Prices and specifications are subject to change without notice

WWW.MIVS.COM

info@mivs.com

Phone 610-754-6800

Fax 610-754-9766

PO Box 331 Boyertown, PA 19512

Manufactured in the USA by MIVS. Revised December 18, 2007