

WARRANTY

MicroImage Video Systems warrants that each VDA206 is free from defects due to faulty materials or improper workmanship for a period of one (1) year. MicroImage Video Systems further warrants that any part which proves defective in materials or workmanship within one (1) year, will be replaced or repaired at no cost to the user. Labor to replace defective parts will be done without charge, provided the equipment is returned to MicroImage Video Systems prepaid, insured and properly packaged. Prior return authorization must be obtained from MicroImage Video Systems.

NOTE

This warranty covers the MicroImage VDA206 Video Distribution Amplifier only.

CONDITIONS

This warranty is void if the warranted part has been altered or subjected to abuse or misuse. Defective parts must be returned to MicroImage Video Systems.

SOLE WARRANTY

This Warranty is in lieu of all other warranties expressed or implied including, without limitation, any implied warranty or any implied warranty of fitness for a particular purpose. MicroImage Video Systems shall have the final right to determination as to the existence and cause of any defect and its appropriate adjustment in accordance with the terms of this warranty. In no event shall MicroImage Video Systems be liable for any consequential or collateral damages.

RETURNS

All returns MUST have an RMA number. Please call, fax or email for an RMA form. The RMA form will have the proper shipping address for returns.

Phone 610-754-6800
Fax 610-754-9766
Email techsupport@mivs.com

S-Video 1x6 DISTRIBUTION AMPLIFIER Operation Manual

Model VDA206

MicroImage Video Systems
division of World Video Sales Co., Inc

PO Box 331
Boyertown, PA 19512
Phone 610-754-6800
Fax 610-754-9766
sales@mivs.com

www.mivs.com

CONTENTS

SPECIFICATIONS	2
UNPACKING	3
CONNECTIONS.....	3
Power	3
Video	3
IN CASE OF DIFFICULTY	3
WARRANTY.....	4
RETURNS.....	4

Rev 0 09-30-1998, Reviewed 07-07-2015

SPECIFICATIONS

Input level	1.0 Vpp Composite, 75 Ω
Output level	Same as respective inputs \pm 2% into 75 Ω
Connectors	
VDA206	4 pin mini-DIN female (std. S-Video conn.)
Bandwidth	Greater than 30Mhz
Temperature	
Operating	0° ~ 40° C (32° ~ 104° F)
Storage	-40° ~ 60° C (-40° ~ 140° F)
Humidity	
Operating	10% ~ 90% (non-condensing)
Storage	5% ~ 95% (non-condensing)
Power	
Voltage	110 ~ 125VAC, 50/60Hz (+12VDC & 230VAC available, contact factory)
Consumption	12W
Size	8.6" (W) x 6.7" (D) x 2.4" (H) 218.5 mm (W) x 170 mm (D) x 61 mm (H)
Weight	1 lb, 15 oz.

Manufactured in USA by MicroImage Video Systems

UNPACKING

The VDA206 package includes the following items:

VDA206 Video Distribution Amplifier
CAB05006 Power Cord
This operation manual

Please inspect all items carefully and report damaged or missing items to your dealer or MicroImage Video Systems.

CONNECTIONS

Power

The VDA206 uses an industry standard, detachable 3 wire power cord which is included with the unit. For medical applications, a special low leakage cord (part # CAB01006) is available. Connect the cord to a suitable power source of 120VAC, 50-60Hz.

Video

Connect the video source (i.e. camera) to the IN connector on the VDA unit. Connect the OUTPUT signals from the VDA unit to the video displays as required. Each output can only have a single 75 ohm termination.

The VDA206 uses industry standard mini-DIN connectors for S-Video.

IN CASE OF DIFFICULTY

If you are experiencing problems with any MicroImage product, you can contact MicroImage Support using the following methods:

Phone	610-754-6800
Fax	610-754-9766
Email	techsupport@mivs.com
Web	www.mivs.com